




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 25/01	A1	(11) International Publication Number: WO 98/39049 (43) International Publication Date: 11 September 1998 (11.09.98)
(21) International Application Number: PCT/US98/04030 (22) International Filing Date: 3 March 1998 (03.03.98) (30) Priority Data: 812,750 6 March 1997 (06.03.97) US (71) Applicant: SCIMED LIFE SYSTEMS, INC. [US/US]; One SciMed Place, Maple Grove, MN 55311-1566 (US). (72) Inventors: CORNELIUS, Richard, G.; 3163 Lafayette Ridge Road, Wayzata, MN 55391 (US). KELZENBERG, An- thony; 501 Westminster Avenue, Watertown, MN 55388 (US). URICK, Michael, J.; 13223 Red Fox Road, Rogers, MN 55374 (US). REYNOLDS, Brian, R.; 14752 Xkimo N.W., Ramsey, MN 55303 (US). (74) Agents: SEAGER, Glenn, M. et al.; Crompton, Seager & Tufte, LLC, Suite 895, 331 Second Avenue South, Minneapolis, MN 55401-2246 (US).		(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>

(54) Title: GUIDE WIRE WITH HYDROPHILICALLY COATED TIP**(57) Abstract**

A guide wire (20) including a lubricious distal portion (22) and a less lubricious intermediate portion (24) proximal of said distal portion. One guide wire provides a highly lubricious distal portion with a hydrophilic layer and a less lubricious intermediate portion with a hydrophobic layer. Another guide wire provides a lubricious distal portion with a polymer tip (36) that is itself hydrophilic. Yet another guide wire provides a less lubricious intermediate portion using a stainless steel coil (42) helically wound around the tapering intermediate portion. The coil is preferably coated with a hydrophobic coating such as PTFE or silicone. The coil can either abut the distal portion proximal end or extend into the distal portion interior.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

GUIDE WIRE WITH HYDROPHILICALLY COATED TIP

Field of the Invention

The present invention relates generally to intravascular guide wires. In particular, the present invention relates to
5 guide wires having a lubricous hydrophilic tip and a less lubricous intermediate portion proximal the distal tip.

Background of the Invention

Guide wires are used in various procedures within various
10 conduits in the body. In particular, they are used in Percutaneous Transluminal Coronary Angioplasty (PCTA) and other coronary procedures. This can involve inserting a guide wire through an incision in the femoral artery near the groin, advancing the guide wire over the aortic arch, into a coronary
15 artery, and across a lesion to be treated. Guide wires can be inserted directly into the vasculature or within a guide catheter. The distal end of the guide wire ultimately lies directly within the vasculature.

Guide wires serve to guide devices into position for both
20 therapeutic and diagnostic purposes. For this to happen, the guide wire itself must be properly positioned. This is difficult, as it involves moving a wire tip through a narrow opening within a narrow vessel, from 180 centimeters away. This task can be especially difficult as the guide wire must
25 be extremely flexible at the distal end to enable the guide wire tip to enter vessel branches at various angles. The extreme flexibility can come at the expense of axial or

rotational strength. Improved responsiveness to remotely applied forces, both rotational and axial, has been provided by reducing friction along the guide wire length. In particular, providing a highly lubricous guide wire distal
5 region of about 12 inches has proven advantageous in maneuvering guide wires through the arteries to reach the site of blockage. Having this same lubricous coating on the tip of the wire has been advantageous in making the wire perform better in finding small openings in the blockages and crossing
10 them.

Once the guide wire tip is in position, devices including catheters are advanced into position over the guide wire and withdrawn over the guide wire. Such catheter movement acts upon, and tends to move, the guide wire contained within.
15 This can tend to dislodge the guide wire tip. Minor patient movement including breathing also acts to move the guide wire as does handling of the guide wire proximal portion extending from the patient. Dislodging the guide wire tip may require repositioning the guide wire, with the attendant time and
20 effort. Once in position, therefore, stability and resistance to applied forces is preferred over the initially desirable ease of movement and responsiveness to applied forces.

What is desirable and has not been provided is a guide wire easily maneuvered into position across a tight lesion,
25 yet providing stability and resistance to movement once the guide wire is in position.

Summary of the Invention

The present invention provides a guide wire having a highly lubricous distal portion, followed proximally by a less lubricous intermediate portion, followed proximally by a proximal portion. The guide wire includes a core member within, preferably formed of metal and having a proximal constant cross section portion, followed distally by a tapered portion, followed distally by a reduced cross section portion. The tapered portion can have multiple tapers. The distal end of the reduced cross section portion is preferably flattened into a ribbon, providing greater flexure in one plane. A preferred core has a circular cross section in the proximal and tapered portions. One guide wire embodiment has a intermediate and distal portion length totalling about 12 to 14 inches. A preferred length for the distal portion is about 1 to 3 centimeters.

A preferred guide wire achieves a lubricous distal portion by having a hydrophilic surface in the distal portion. A less lubricous intermediate portion is achieved by having a hydrophobic surface in the intermediate portion. The hydrophilic surface has a very low coefficient of friction when placed against an artery wall in a blood filled artery. The hydrophobic surface has a higher coefficient of friction against the artery wall.

The present invention distal portion can be formed of a polymer not necessarily hydrophilic, but having a hydrophilic

coating thereover. The intermediate portion can be formed of a hydrophobic polymer sleeve over the core wire or a polymer sleeve over the core wire having a hydrophobic coating. In another embodiment, the intermediate portion can include a
5 coil around the core wire, the coil preferably having a hydrophobic coating. The coil wire abuts the distal portion in one embodiment, and is embedded beneath the distal polymer in another embodiment. In yet another embodiment, the distal portion includes a distal tip having a proximally tapered
10 proximal portion, and the coil wire distal end contacts the distal tip in the tapered portion, thereby centering the coil.

The present invention provides the ability to cross tight lesions by having a highly lubricous, low friction, distal portion, which is relatively easy to slide through a narrowed
15 vessel region. The extremely lubricous portion is limited to a shorter length relative to previous devices. A preferred length is about 1 inch. The lubricity is limited to the portion where the extreme lubricity is most needed, the distal portion. Lower friction is required in the extreme distal
20 portion because the core member there is narrower and therefore weaker, not having the strength of the more proximal portion to handle being axially pushed from the proximal end against obstructions. Low friction is also required in this portion because this is the portion that is required to
25 initially cross an extremely tight lesion, something not required of the more proximal portion. The low friction

facilitates the wire tip first piloting into the small remaining opening in the lesion and then crossing the lesion without buckling the wire.

To counteract the highly lubricous, low friction distal portion, the present invention deliberately provides a less lubricous, higher friction intermediate portion, proximal of the distal portion. The intermediate portion can lie against an artery wall, or guide catheter wall, "anchoring" the guide wire. The present invention, by having an anchoring portion proximal of the distal portion, provides resistance to forces such as catheter movement over the guide wire, which could act to dislodge the guide wire tip from its desired position.

While the anchoring portion friction will not prevent all movement of the guide wire, it provides sufficient static friction to resist unintentional movement due to either catheter movement or patient movement. In this way, a series of minor forces acting on the guide wire proximal portion, if below the threshold of static friction presented by the anchoring portion, will not be translated into a series of minor movements of the guide wire distal tip.

Brief Description of the Drawings

Figure 1 is a fragmentary, side cross-sectional view of a guide wire, in accordance with the present invention, having a coil in the intermediate portion;

Figure 2 is a fragmentary, side cross-sectional view of a second embodiment of a guide wire having a core wire shown in phantom;

Figure 3 is a fragmentary, side cross-sectional view of a third embodiment of a guide wire having a coil extending into the distal tip;

Figure 4 is a fragmentary, side cross-sectional view of a fourth embodiment of a guide wire having a two part coil extending into the distal tip; and

Figure 5 is a fragmentary side cross-sectional view of a fifth embodiment of a guide wire having a proximally tapered polymer tip and a coil sitting on the taper.

Detailed Description of the Preferred Embodiments

Figure 1 illustrates a fragmentary, side cross-sectional view of a guide wire 20 having a distal portion 22, an intermediate portion 24, and a proximal portion 26. Guide wire 20 has a surface extending the length thereof, as indicated at 21. The length of distal portion 22 is indicated by arrows 40 and the length of intermediate portion 24 by arrows 44. Guide wire 20 includes an elongate core member 28 having a constant cross section portion 30, a tapered portion 32 and a reduced cross section portion 34. Core member 28 preferably has a circular cross section in portions 30 and 32. The intermediate tapered portion 32 may comprise a single taper or a series of tapers with regions of constant diameter

in between. Core 28 is preferably formed from high tensile strength stainless steel wire or a super-elastic alloy such as Nitinol.

Core reduced cross section portion 34, illustrated lying
5 within a distal portion 22, provides extreme flexibility to the guide wire where needed, at the extreme distal end. Reduced cross section portion 34 is preferably flatter in one dimension than another, forming a ribbon, providing more flexibility in one dimension than another. Tip flexibility is
10 desirable for insinuating the guide wire into ever more distal and tortuous coronary arteries. The embodiment of distal portion 22 illustrated can include a distal tip 38 encasing core reduced cross section portion 34. In a preferred embodiment, distal tip 38 includes a polymeric material.
15 Distal tip 38 is preferably radiopaque to allow for tracking the tip position using fluoroscopy. In one embodiment, tip 38 includes polyurethane and is loaded with tungsten, 85 to 90 percent by weight, for radiopacity. In one embodiment, a polyurethane sleeve forms distal tip 38, which can be between
20 about 1/2 and 7 centimeters in length. In a preferred embodiment, tip 38 is between 1 and 3 centimeters in length.

Distal portion 22 according to the present invention is lubricous. In a preferred embodiment, distal portion 22 is extremely lubricous. In one embodiment, the lubricity is
25 provided by having a hydrophilic material at the surface of distal portion 22. A hydrophilic surface makes the surface

highly lubricous when in contact with a water based fluid such as blood. In the embodiment illustrated in Figure 1, lubricity is provided by a distal layer 36 over reduced diameter portion 34 and distal tip 38. A hydrophilic coating
5 over the guide wire presents very little friction when sliding through the artery interior. This provides ease of crossing tight lesions, allowing difficult and distally remote lesions to be treated. In one embodiment, distal layer 38 includes a polyvinylpyrrolidone (PVP) coating. In another embodiment,
10 distal layer 38 includes a polyethyl maleic anhydride coating. In a preferred embodiment, distal portion 22 is about 0.014 inches in diameter.

Proximal of distal portion 22 is intermediate portion 24 which has a lubricity less than that of distal portion 22. In
15 a preferred embodiment, intermediate portion 24 has length 44 of about 20 to about 30 centimeters. In one embodiment, intermediate portion 24 is about 28 centimeters long and about 0.0130 to 0.0135 inches in diameter. Guide wires used to deliver stiffer devices may have a shorter intermediate region
20 to make the wire more supportive. In these cases intermediate portion 24 may be as short as 3 centimeters. In the embodiment depicted in Figure 1, intermediate portion 24 includes tapered core portion 32 which is encased in a coil 42. A preferred coil is formed of stainless steel and coated
25 with hydrophobic coating. A preferred hydrophobic coating is PTFE or silicone. Coil 42, by presenting a series of wires

oriented transversely to the axial direction of guide wire movement, provides resistance to axial movement. The coil also provides increased pushability and kink resistance for tapered core portion 32. In compression, the coil provides
5 axial strength over the length of tapered core portion 32 which decreases in strength with decreasing core cross section. The distal end of coil 42 can be attached to core 28 using solder or adhesive. The proximal end of coil 28 is preferably secured to core 28 by adhesive.

10 Intermediate portion 24 provides a higher friction anchoring portion to maintain the position of distal portion 22. If too much of the guide wire is extremely lubricous, the distal tip can be difficult to fix exactly in position, as catheter advancement and retraction over the guide wire can
15 apply forces to the guide wire, tending to move the guide wire tip. Patient movement, including breathing, can also translate into movement at the guide wire distal tip. By providing an intermediate region having a less lubricous surface, an intermediate anchoring region is provided, which
20 presents friction against the vessel wall, presenting resistance to forces that would otherwise be translated into movement at the distal tip. While the intermediate anchoring portion cannot resist all forces applied to the guide wire and prevent all tip movement, the static friction of the anchored
25 guide wire intermediate portion does provide a threshold barrier to lower level forces. Thus, a series of small forces

is not necessarily translated into a series of low level movements of the guide wire tip.

Proximal portion 26 in a preferred embodiment, extends to the guide wire proximal end. Included in proximal portion in
5 Figure 1 is constant cross section core portion 30. In a preferred embodiment, proximal portion 26 includes a stainless steel wire about 0.013 inches in diameter and has a polytetrafluoroethylene (PTFE) coating. In one embodiment, proximal portion 26 is less lubricous than intermediate
10 portion 24. In another embodiment, proximal portion 26 is more lubricous than intermediate portion 24 but less lubricous than distal portion 22.

Figure 2 illustrates another embodiment of the invention, guide wire 120, having a proximal portion 126, an intermediate
15 portion 124, and a distal portion 122. Distal portion 122 is preferably about 1/2 to 7 centimeters in length, and intermediate portion 124 can be 1 to 15 inches in length and is preferably about 8 to 12 inches in length. Within guide wire 120 is a core 128 having a constant diameter portion 130,
20 a tapered portion 132 and a reduced diameter portion 134. Core 128 can be substantially similar to core 28 discussed with respect to Figure 1. Guide wire 120 has a lubricous distal portion 122 and a less lubricous intermediate portion 124. In the embodiment depicted in Figure 2, distal portion
25 122 includes a distal tip 136. Distal tip 136 can be similar to distal tip 36 in Figure 1. In some embodiments, distal tip

136 is formed of polyurethane, and coated with hydrophilic coatings as discussed above with respect to Figure 1. Distal tip 136 is preferably radiopaque to allow for tracking the tip position using fluoroscopy. In one embodiment, tip 136 includes polyurethane and is loaded with tungsten, 85 to 90 percent by weight, for radiopacity. Distal tip 136 is preferably more radiopaque than intermediate portion 124.

Intermediate portion 124 provides a less lubricous portion proximal to lubricous distal portion 122, as in the embodiment of Figure 1, but without requiring a coil. The lower lubricity is provided by having a hydrophobic surface. This can be provided with both hydrophobic sleeves and hydrophobic coatings over sleeves that are not necessarily hydrophobic. Sleeve 142, illustrated encasing tapered core portion 132, can be formed of a hydrophobic polymer. Hydrophobic polymers include fluorinated ethylene propylene (FEP) and polytetrafluoroethylene (PTFE). Intermediate portion 124 can also be formed of a material such as polyether block amide (PEBAX) or polyethylene coated with a low friction, hydrophobic coating such as silicone, paralene, PTFE, or FEP. Guide wire 120 can be formed by sleeving tube 142 over core 128, bonding the tube in place at its proximal end with adhesive, shrinking a suitable distal tip material over reduced diameter core portion 134, and bonding the distal portion of sleeve 142 to the proximal portion of the distal tip. Another suitable method includes heat shrinking a

polymeric tube over core 128, grinding the tube to an approximate diameter of about 0.0130 to 0.0135 inches, then selectively coating intermediate portion 124 and possibly distal portion 122 also, with one of the hydrophobic coatings, and then coating distal portion 122 with one of the previously described hydrophilic coatings.

Figure 3 illustrates yet another embodiment of the invention, a guide wire 220, having proximal portion 226 followed distally by intermediate portion 224 followed distally by distal portion 222. A core 228 proceeds distally from a constant diameter portion 230 to a tapered portion 232 to a reduced diameter portion 234. Intermediate portion 224 includes a coil 242 surrounding the tapered portion of the core, with coil 242 proceeding distally from a constant diameter portion 241 to a tapered portion 243 to a reduced diameter portion 244. Core 228 is preferably flattened into a ribbon shape in reduced diameter portion 244. Reduced diameter portion 244 is embedded within distal tip 238 when the polymer tip is shrunk onto the wire. In this embodiment, neither solder nor adhesive are required to secure the distal end of coil 242 to core 228. The proximal end of coil 242 can be secured to core 228 by soldering. Distal tip 238 can be coated with a hydrophilic layer 236 as discussed above with respect to the embodiment of Figure 1. The materials of distal tip 238 and layer 236 can be similar to those of distal tip 38 and layer 36.

Figure 4 illustrates yet another embodiment of the invention, a guide wire 320, having a proximal portion 326, followed by an intermediate portion 324, followed distally by a distal portion 322. A core 328 proceeds distally from a constant diameter portion 330 to a tapered portion 332, to a reduced diameter portion 334. A coil 342 surrounds core 328 over the intermediate and distal portions. In the embodiment shown, coil 342 is formed of a proximal coil 323 and a distal coil 325 soldered together at 340. Proximal coil 323 is preferably formed from a less radiopaque material such as stainless steel. This coil can be coated with a hydrophobic coating such as PTFE. Distal coil 325 is preferably formed of a more radiopaque material such as platinum. Combined coil 342 is attached to core 328 proximally with solder at 341 and distally with either solder or welding at 338. A hydrophilic coating 336 is applied to the distal portion of distal coil 325 in one embodiment by first applying a Tie layer polymer such as polyurethane by dip or spray coating, followed by applying a hydrophilic coating over the Tie layer coating. The hydrophilic coating can be one of the coatings described previously with respect to guide wire 20 in Figure 1.

Figure 5 illustrates yet another embodiment of the invention, a guide wire 420 having a proximal portion 426, followed by an intermediate portion 424, followed distally by a distal portion 422. A core 428 proceeds distally from a contact diameter portion 430 to a tapered portion 432, to a

reduced diameter portion 434. A distal tip 436, preferably formed of a polymeric substance, surrounds core reduced diameter distal portion 434. Distal tip 436 includes a tapered portion 437, which tapers proximally toward core tapered portion 432. Guide wire 420 includes a coil 442 which extends distally over core tapered portion 432. Coil 442 has a distal end 443 which contacts and terminates within distal tip tapered portion 437. Coil 442 is thus always centered on core 428, as transverse movement of coil distal end 443 is opposed by distal tip tapered portion 437. Tip 436 can be heated to embed end 443 therein.

While use of the present invention can be described with reference to any of the embodiments, the embodiment of Figure 1 is selected for further illustration. In use, core reduced diameter portion 34 can be bent by the treating physician, prior to insertion into the patient. Having a bent distal tip allows orienting the tip for insertion into arteries by rotating the proximal end of the guide wire, which rotates the bent distal tip toward arterial side branches. The guide wire can be advanced through a guide catheter or directly through the vasculature. After having advanced the guide wire into a coronary artery such as the left coronary artery, the guide wire is maneuvered into selected smaller arteries. In attempting to insinuate the distal most portion of the guide wire into smaller arteries, the lubricous tip provides easier initial advancement into the artery. When a lesion is to be

crossed, lubricous distal portion 22 provides low resistance to axial movement into and through a narrow passage. Low resistance is advantageous as there is less tendency for core reduced diameter portion 34 to kink or buckle when pushed by
5 the treating physician from the extreme proximal end.

Once distal portion 22 is across the lesion, it is highly preferred that the guide wire tip position not change, despite minor changes in proximal handling of the guide wire, movement of other devices over the guide wire, patient breathing, blood
10 flow, and minor changes in frictional conditions along the guide wire length. The present invention allows a guide wire to resist these forces by having intermediate portion 24 lie against and be "anchored" to the vessel or guide catheter wall, presenting a higher quantity of static friction that
15 must be overcome to dislodge the guide wire distal tip, than presented with wires having longer lubricous distal surfaces. The present invention thus makes it less likely that the guide wire will move inside the artery unless the physician is directly intending to move it.

20 The combination of lubricous distal portion and less lubricous intermediate portion thus serves to promote ease of distal tip advancement across tight lesions while stabilizing the distal tip position once placed, allowing other devices to be accurately guided into position by the guide wire.

25 Numerous advantages of the invention covered by this document have been set forth in the foregoing description. It

will be understood, however, that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of parts without exceeding the scope of the invention. The
5 inventions's scope is, of course, defined in the language in which the appended claims are expressed.

What is claimed is:

1. A guide wire having a distal end and a proximal end comprising:

an elongate core;

a lubricous distal portion;

an intermediate portion, proximal of said distal portion, said intermediate portion being less lubricous than said distal portion; and

a proximal portion proximal of said intermediate portion.

2. A guide wire as recited in claim 1, wherein

said guide wire includes a surface,

said distal portion surface is hydrophilic, and

said intermediate portion surface is hydrophobic.

3. A guide wire as recited in claim 2, wherein

said distal portion surface includes a hydrophilic coating.

4. A guide wire as recited in claim 2, wherein

said distal portion surface includes a hydrophilic coating, and

said intermediate portion surface includes a hydrophobic coating.

5. A guide wire as recited in claim 4, wherein said proximal portion includes a lubricous coating over said elongate core.

6. A guide wire as recited in claim 5, wherein said proximal lubricous coating is polytetrafluoroethylene.

7. A guide wire as recited in claim 1, wherein said guide wire includes a surface, said distal portion surface is hydrophilic, and said intermediate portion includes a coil around said elongate core.

8. A guide wire as recited in claim 7, said distal portion including a polymeric distal tip having a proximally tapered proximal portion, said coil having a distal end, wherein said coil distal end contacts said distal tip within said tapered portion.

9. A guide wire as recited in claim 7, wherein said intermediate portion coil includes a hydrophobic coating.

10. A guide wire as recited in claim 9, wherein said elongate core is tapered distally within said intermediate portion.

11. A guide wire as recited in claim 10, wherein said coil comprises stainless steel having a silicone coating.

12. A guide wire as recited in claim 10, wherein said coil comprises stainless steel having a polytetrafluoroethylene coating.

13. A guide wire as recited in claim 10, wherein said coil includes a distal tapered portion, said coil tapered portion extending within said guide wire distal portion.

14. A guide wire having a distal end and a proximal end comprising:

an elongate core having a length and a cross section, said core having a distal reduced cross section portion;

a tapered portion proximal of said reduced cross section portion; and

a proximal uniform cross section portion, said core having a surface extending the length thereof, said reduced cross section portion having means for providing low friction, said tapered portion having means for providing higher friction than said reduced cross section portion friction.

15. A guide wire as recited in claim 14, wherein said means for providing higher friction includes a wire coil about said core tapered portion.

16. A guide wire as recited in claim 15, said distal end including a polymeric distal tip having a proximally tapered proximal portion, said coil having a distal end, wherein said coil distal end lies within said distal tip tapered portion.

17. A guide wire as recited in claim 15, wherein said means for providing low friction includes a lubricous layer over said reduced cross section portion surface, and

said coil includes a less lubricous layer over said coil.

18. A guide wire as recited in claim 14, wherein said means for providing low friction includes a lubricous layer over said reduced cross section portion surface; and

said means for providing higher friction includes a less lubricous layer over said tapered portion surface.

19. A guide wire as recited in claim 18 wherein said lubricous layer includes a hydrophilic material.

20. A guide wire as recited in claim 18, wherein said less lubricous layer includes a hydrophobic material.

21. A guide wire having a distal end, a proximal end, a length, and a surface extending over said length comprising:

an elongate core;
a distal portion;
an intermediate portion proximal of said distal portion;
means for providing low friction over said distal portion
surface; and
means for providing higher friction over said
intermediate portion surface, said higher friction being
higher than said distal portion friction.






Fig. 4





Fig. 5



INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/04030

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61M25/01

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 661 073 A (TERUMO CORP) 5 July 1995 see column 3, line 51 - column 10, line 33; figure 1	1,7,14, 18,19,21
A	---	2
X	EP 0 519 604 A (SCIMED LIFE SYSTEMS INC) 23 December 1992	1,7,21
A	see column 2, line 36 - column 5, line 48; figure 1 see column 7, line 12 - column 7, line 48; figure 3	2,14
A	WO 96 34635 A (ADVANCED CARDIOVASCULAR SYSTEM) 7 November 1996 see page 4, line 15 - page 5, line 10; figure 1	1,14,21
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

3 July 1998

Date of mailing of the international search report

13/07/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Jameson, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/04030

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 0 744 186 A (TARGET THERAPEUTICS INC) 27 November 1996 see abstract; figure 1 -----</p>	<p>1,14,21</p>

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 98/04030

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0661073 A	05-07-1995	NONE	
EP 0519604 A	23-12-1992	CA 2068584 A,C DE 69213353 D DE 69213353 T JP 5168717 A US 5452726 A US 5443907 A	19-12-1992 10-10-1996 30-01-1997 02-07-1993 26-09-1995 22-08-1995
WO 9634635 A	07-11-1996	EP 0828524 A	18-03-1998
EP 0744186 A	27-11-1996	AU 5454696 A CA 2177426 A JP 9099092 A NO 962134 A	19-12-1996 27-11-1996 15-04-1997 27-11-1996